(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 19 February 2004 (19.02.2004)

PCT

(10) International Publication Number WO 2004/015515 A3

(51) International Patent Classification7: G06F 12/14, G11C 16/22, 11/412

(21) International Application Number:

PCT/SG2002/000227

(22) International Filing Date: 4 October 2002 (04.10.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: PCT/SG02/00171

31 July 2002 (31.07.2002) SG

(71) Applicant (for all designated States except US): TREK 2000 INTERNATIONAL LTD. [SG/SG]; 30 Loyang Way #07-13/14/15. Loyang Industrial Estate, Singapore 508769 (SG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): OOI, Chin, Shyan,


Raymond [MY/SG]; Blk 438, Tampines St. 43 #08-157, Singapore 520438 (SG). LIM, Lay, Chuan [MY/SG]; Blk 322, Bukit Batok St. 33 #03-04, Singapore 650322 (SG). POO, Teng, Pin [MY/SG]; Blk 44 Bedok South Road #11-763, Singapore 460044 (SG). TAN, Henry [SG/SG]; 1 Palm Drive, Singapore 456458 (SG).

(74) Agent: WATKIN, Timothy, Lawrence, Harvey; Lloyd Wise, Tanjong Pagar, P.O. Box 636, Singapore 910816

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR AUTHENTICATION



(57) Abstract: An authentication system (10) to verify a password is provided. The authentication system includes a first storage unit (16) to store an authentication sequence (24) and a read-only memory unit (18) on which an authentication algorithm (26) is programmed. A microcontroller (20) is coupled to the first storage unit, the read-only memory unit and a web server. The microcontroller receives the password and executes the authentication algorithm to verify the password with the authentication sequence. A second storage unit (22) is coupled to the microcontroller to store data from the web server. Access to a second storage unit is permitted by the microcontroller only if the password has been verified.